

ALUMINIUM RAMPS




FEATURES & BENEFITS

- **Light and Durable**

The sturdy aluminium ramps are durable and lightweight for easy handling. These ramps are designed with deep ridge treads for better traction that enables safe and efficient loading and unloading of the MultiOne from trucks and trailers.

NOTE: When ordering, please specify the machine model, weight, and wheelbase.



Model	Loading capacity per pair	
	Machine wheelbase 100 cm (39 in)	Machine wheelbase 150 cm (59 in)
250	2500 kg (5511 lbs)	3800 kg (8377 lbs)
300	1900 kg (4189 lbs)	2500 kg (5511 lbs)
350	2000 kg (4409 lbs)	2500 kg (5511 lbs)
400	2290 kg (5048 lbs)	2750 kg (6062 lbs)
450	1070 kg (2359 lbs)	1250 kg (2756 lbs)
500	2575 kg (5677 lbs)	2945 kg (6493 lbs)

Model	Length	Internal Width (A)	External Width (B)	Weight	Code
250	250 cm (98.4 in)	34 cm (13.4 in)	40 cm (15.7 in)	43 kg (95 lbs)	C890790
300	300 cm (118 in)	34 cm (13.4 in)	40 cm (15.7 in)	52 kg (115 lbs)	C890791
350	350 cm (138 in)	34 cm (13.4 in)	40 cm (15.7 in)	62 kg (137 lbs)	C890792
400	400 cm (157.5 in)	34 cm (13.4 in)	40 cm (15.7 in)	56 kg (123 lbs)	C890793
450	450 cm (177.2 in)	34 cm (13.4 in)	40 cm (15.7 in)	78 kg (172 lbs)	C890794
500	500 cm (197 in)	34 cm (13.4 in)	40 cm (15.7 in)	86 kg (190 lbs)	C890795